

# Lift&Drive 90IE

Simple but tough







## Capability when you need it

Lift&Drive 90IE is a simple but capable lifting trolley, wider and longer chassis compared to the ECO range. It's easy to use and easy to stow away, making it ideal for work environments like canteens and kitchens, offices, libraries, or shops – as well as more industrial applications.

The trolley is smooth and stable to use, with a lifting capacity of 90 kg. The handlebars are easily adjusted to suit any operator, and safety features such as overload

protection and safety clutch make the trolley safe to use also by inexperienced operators. Thanks to the motor brake, loads can be kept in an elevated position for longer.

Low roll resistance combined with optimal weight to capacity ratio enables ergonomic and safe lifting without risk of strain. The durable, high-quality build requires only minimal maintenance.



### Travel lightly

Don't move around more weight than needed. With optimised weight to capacity ratio, total weight is kept at a minimum.



### Cleanability for hygienic work

Easy-to-clean stainless-steel design option, combined with a specially designed mast curtain, contributes to easy cleaning as well as low particle emissions during operation.



### Get the solution to your need

Your optimal solution is determined by the task, the load, the operator, and the work environment. With a wide range of options, and tools, Pronomic can customise a solution that fits your needs and solves your problems.



### Easy roll with heavy loads

A lifting trolley with low roll resistance makes it easier to move heavy loads, further reducing the strain on your body.



### When reliability and precision is key

Our unique, spindle-based lifting system enables speedy and precise lifting and lowering of your load. While saving time, it also adds safety and reliability, with minimal maintenance requirements.



### Manoeuvrability in tight spaces

Swivel wheels give a very narrow turn radius, making the trolley easy to steer.



### Ergonomic handgrip for all

Be sure to reduce the strain on muscles and joints during operation by adjusting the handlebars to the optimal working height.

### Low build

Fits under pallets, adapted for loading and unloading goods.

- Reliable high-quality design with minimum maintenance needs
- Compact design to fit any space
- Small footprint when parked
- Easy and safe to use also for inexperienced operators
- Adjustable to suit different operators
- Welded, high polished stainless steel chassis option: easy to clean
- Economic choice for simpler industrial applications

### Basic data

Height* (mm)	Min 1433 Max 2183
Length (mm)	764
Width (mm)	550
Net weight (kg)	33
Maximum load including tool (kg)	90
Max lifting speed empty/full (m/min)	5
Safety	CE
Battery	Sealed, valve regulated, lead-acid batteries (VRLA)
Nominal battery voltage	24V DC (12V x 2)
Battery capacity	7.2 Ah
Stainless steel option	Yes



**PRONOMIC AB**

Box 5504  
192 05 Sollentuna  
Sweden  
+46 (0) 8 544 706 60  
[sales@pronomic.com](mailto:sales@pronomic.com)  
[pronomic.com](http://pronomic.com)

**TILTECH NV**

Vriesenrot 22  
9200 Dendermonde  
Belgium  
+32 52 40 95 70  
[info@tiltech.be](mailto:info@tiltech.be)  
[www.tiltech.be](http://www.tiltech.be)

Smart moves  
for safe work